

## 2.0Megapixel IP Camera



# IP CAMERA

## KW-IP 95

### MAIN FEATURES

---

- ☐ 1/3"Progressive Scan CMOS
- ☐ H.264 main profile compression
- ☐ Support IR-CUT filter switch to achieve day and night monitoring
- ☐ Support smart mobile&network Surveillance
- ☐ Support network user management,
- ☐ Compatible with ONVIF standard
- ☐ Support real-time remote monitoring playback and downloading;

# IP Camera

## Order information

### KW-IP 95



| Camera                  | KW-IP 95                                                                         |
|-------------------------|----------------------------------------------------------------------------------|
| Image Sensor            | 1/3" Progressive Scan CMOS                                                       |
| Signal System           | PAL/NTSC                                                                         |
| Effective Resolution    | 1920x1080 (2,073,600 Pixel)                                                      |
| Minimun Illumination    | Color:0.01Lux@(F1.2,AGC ON),0 LUX with IR                                        |
| Electronic Shullter     | 1/50(1/60)s-1/100,000s                                                           |
| Lens                    | 2.8-12mm MegaPixel Manual Varifocal lens                                         |
| Day/Night               | Support IR-CUT                                                                   |
| IR Distance             | 42pcs IR LED,45Meter IR Distance                                                 |
| Synchronization way     | Internal Synchroniztion                                                          |
| Video Output            | 1Vp-p Composite Output(75Ω/BNC)                                                  |
| S/N Ratio               | >48dB                                                                            |
| Video Compression       | H.264 Main Profile, JPEG Capture                                                 |
| Video Bite Rate         | 32 Kbps~8Mbps                                                                    |
| Wide Dynamic Rangee     | Digital Support                                                                  |
| Frame Rate              | 50Hz:25fps(1920*1080)<br>60Hz:30fps(1920*1080)                                   |
| Storage                 | Support network storage                                                          |
| Intelligent Alarm       | Motion detect, Video loss, Network storage<br>IP Address conflict                |
| Protocols               | TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE, SMTP, NTP<br>(HTTPS,SIP ,802.1x,IPv6 Optional) |
| Basic                   | Anti-flicker, Dual stream, Heartbeat, Password protection                        |
| Communication Interface | 1 RJ45 10M/100M Base-T self-adaptive Ethernet interface                          |
| Video Output            | 1Vp-p Composite Output(75Ω/BNC)                                                  |
| Operating Condition     | -10°C~60°C, Humidity 90% or less(non-condensing)                                 |
| Power Supply            | DC12V ±10%                                                                       |
| Weatherproofing         | IP 66                                                                            |