

1.0Megapixel IP Camera



IP CAMERA

KW-IP 102

MAIN FEATURES

- ☐ 1/3" Progressive Scan CMOS
- ☐ Hi3518E, Megapixel CMOS Sensor
- ☐ 4mm MegaPixel fixedlens
- ☐ 2pcs high intensity Array LED,20M IR Distance
- ☐ Full Real-time:720P@25FPS
- ☐ IR-CUT filter switch to achieve day and night
- ☐ Compatible with ONVIF standard
- ☐ Vandalproof IR Dome Camera

IP Camera

Order information

KW-IP 102



Camera	KW-IP 102
Image Sensor	1/3" Progressive Scan CMOS
Signal System	PAL/NTSC
Effective Resolution	1280x720
Minimun Illumination	Color:0.01Lux@(F1.2,AGC ON),0 LUX with IR
Electronic Shullter	1/50(1/60)s-1/100,000s
Lens	4 mm Megaixel Fixed Lens
Day/Night	Support IR-CUT
IR Distance	2PCS High Intensity Array IR LED
	20 Meter IR Distance
Synchronization way	Internal Synchroniztion
Video Output	1Vp-p Composite Output(75Ω/BNC)
S/N Ratio	>48dB
Video Compression	H.264 Main Profile, JPEG Capture
Video Bite Rate	32 Kbps~8Mbps
Max. Resolution	1280*720
Frame Rate	50Hz:25fps(1920*720), 60Hz:30fps(1920*720)
Storage	Support network storage
Intelligent Alarm	Motion detect, Video loss, Network storage
	address conflict
Protocols	TCP/IP, HTTP,DHCP, DNS, PPPoE, SMTP, NTP
	(HTTPS, SIP,802.1x, IPv6 Optional)
Basic	Anti-flicker, Dual stream, Heartbeat, Password protection
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet interface
Video Output	1Vp-p Composite Output(75Ω/BNC)
Operating Condition	-10°C~60°C, Humidity 90% or less(non-condensing)
Power Supply	DC12V ±10%