

2.0Megapixel IP Camera



IP CAMERA

IP-TPOWER S7

MAIN FEATURES

- ☐ 1/2.8" Mega Pixel CMOS
- ☐ IR distance 150 m , IR light control
- ☐ Backlight compensation ON/OFF
- ☐ Efficient cooling structure
- ☐ Resolution 1080P
- ☐ Focus length 5-90 mm
- ☐ Support ,ONVIF
- ☐ IP66



IP Camera

Order information

IP-TPOWER S7



Camera	IP-TPOWER S7
Image Sensor	1/2.8 CMOS
Signal Model	PAL/NTSC
Horizontal Resolution	1080P
Effective Pixel	1920(H)x1080(V)
Minimun Illumination	Color:0.01Lux ,W:0.001Lux
S/N Radio	>60dB
Backlight Compensation	on/off
White Balance	Auto
Electronic shutter	PAL:1/25~1/10000s NTSC:1/30~1/100000s
Focus Length	5~90mm
Optical Focus	22x
Focus System	Auto/Manual
IR distance	150M
IR light control	Intelligent control technology
IR light angle	Intelligent zoom matching technology
IR light power	Manual setting
IR on	Day/Night/Auto/Timing
IR life	30000 hours
Horizontal range	360 ° Continuous rotation
Vertical range	-90 ° ~0 °
Preset call Speed	Max 200 ° /S
Manual Call Speed	0.01 ° ~ 180 ° /S
Presets	255
Cruise track	8 groups, each group for 16 presets
Patrol track	4 groups, each group record 3 mins
Video compression	H.264 Main Profile encoding; MJPEG/ JPEG Baseline encoding
Audio compression	G.711, G.726
Primary stream	1920*1080 25fps
Secondary stream	VGA, QVGA, 25fps
Video bit rate	32Kbps 16Mbps continuously adjustable, support CBR/ VBR
Network protocol	TCP/ IP, UDP,RTP,RTSP,RTCP,HTTP,DNS DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP

IP Camera

Camera	IP-TPOWER S7
ONVIF Support	Support
Cooling Structure	Dustproof structure outside the circle
Power Supply	DC12V(4A)
Power	35W
Work Temperature	-35-65
IP Rating	IP 66