

CCTV Competitive Hybrid Network DVR

TVI 5MP+AHD 1080p+CVI 1080p+960H/D1+IP Camera



RMH-0428EU-101C3

- Up to 5MP (2592 x 1920) TVI camera supported
- Support TVI, AHD, CVI analog camera and IP Camera
- Support OSD setting over coaxial (UTC)
- Support IP camera with Onvif Profile protocol (V2.4)
- Cross device function for redundant recording
- Ideal for project bid, public place like airport, bank, and administration
- Excellent picture quality



MADE IN TAIWAN

CE FC RoHS

RMH

Competitive

RMH-0428EU-101C3

Front Panel : 1



Rear Panel : E-1



Dimension (mm) : 250(w)x215(d)x45(h)

Model		RMH-0428EU-101C3
Camera Input		4CH AHD ,TVI ,CVI, IPC Hybrid
Housing		1
Video	Input	TVI:5MP@12/10 fps, 4MP@15/12 fps, 3MP@18/15 fps, 1080p@30/25 fps, 720p@60/50 fps, 720p@30/25 fps AHD:1080p@30/25 fps, 720p@60/50 fps, 720p@30/25 fps CVI:1080p@30/25 fps, 720p@60/50 fps, 720p@30/25 fps 960H/D1
	Output	1 HDMI with Audio and 1 VGA (Max. 1920 x 1080)
Audio	Input	4 RCA
	Output	1 RCA
System	Operating System	Embedded Linux OS
	SATA Devices	Max. 1 x SATA Device (HDD x 1)
	External HDD	N/A
	Alarm In /Relay Out	N/A
	Serial Interface	RS-485
	USB 2.0 Ports	USB2.0 X2
	Dimension (mm)	250mm(W)X215mm(D) X45mm(H)
	Power Rating	12V 2A, 24W
Display	Split Screen	1,4, SEQ.
	Auto Channel Switching	Switching time : 1 ~ 99 sec
	Mode	Zoom, Auto SEQ.
	Compression	H.264 High Profile
Recording	Main (Recording) Resolution	2590 x 1920, 2590 x 1520, 2048 x 1520, 1920 x 1080, 1280 x 720; 944 x 480 .704 x 480, 352 x 240 (NTSC) / 944 x 576 ,704 x 576, 352 x 288 (PAL)
	Sub (Network) Resolution	640 x 360 / 352 x 240, 176 x 120 (NTSC) / 352 x 288, 176 x 144 (PAL)
	Picture Quality	10~100 levels for adjustment
	Mode	Continuous, Event, Schedule
	Record Rate	NTSC 5MP 24fps ; 4MP 30fps ; 3MP 40fps ; 1080p 60fps ; 720p 120fps NTSC 5MP 20fps ; 4MP 25fps ; 3MP 33fps ; 1080p 50fps ; 720p 100fps
	Pre-Alarm	1 ~ 5 SEC
	Post-Alarm	1 ~ 100 SEC
Playback	Search Mode	Date/time, Event
	Zoom	*Digital (x2 ~ x5)
Network	Network Interface	10/100 Ethernet
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS
	Application	Windows 7 & 8, Mac OS X
	Remote Software	SoCatch, IE Browser, iCMS Pro
	Account	1 Admin + 10 Users
	Mobile Device	Windows Phone 7.8, iPhone, iPad, Android
Backup	Interface	USB or SATA
	AudioBackup	YES
	Backup Type	Network, ext. USB flash device , SATA optical DVD..etc.
Alarm	Motion Detection	Sensitivity: 100 levels for each channel Area: Programmable individually
	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)
OSD&DVR Control	Multi-Language	Supported
	Camera Title	Multi-Language
	USB Mouse	YES
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)
	Remote Controller	IR Remote Control
	System Upgrade	USB Flash Drive, iWatch DVR
	Pan/Tilt/Zoom Control	Control From RS485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)
General	Operating Temperature	-10°C ~ +55°C (14°F ~ 131°F)
	Operating Humidity	10%~80%

All specifications are subject to change without notice.



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.
106 ถ.พระรามที่2 แขวงราม2 เขตจตุจักร กรุงเทพมหานคร 10150
106 Soi Rama II 42, Rama II Rd., Bangmod Jomthong Bangkok 10150

TEL: 02-898-6470-1
FAX: 02-898-6470#13
WWW.ABT-THAI.COM