

SUPERB PERFORMANCE,



- 25% faster print speed of up to 7.9" per second
- 2 colour printing for logos and graphics
- Improved spill resistant cover for added durability
- Ease-of-use features including drop-in paper loading, long-lasting autocutter and auto status back messages

SPECIFICATIONS

Thermal Line Printing

Weight - approx. 1.8 kg



PRINT METHOD

Terminal Module Thermal Printer

TM-T88IV

PRINT FONT	FONT		9 x 17 / 12 x 24
	COLUMN CAPACITY (COLUMNS) CHARACTER SIZE (MM) CHARACTER SET		56 / 42 0.99 (W) x 2.4 (H) / 1.41 (W) x 3.39 (H) 95 Alphanumeric, 37 International, 128 x 11
			Graphic, Traditional / Simple Chinese,
			Japanese, Korean, Thai
		BARCODE	UPC-A/E, CODE 39 / 93 / 128, EAN 8 / 13,
			ITF, CODABAR
		TWO-DIMENSIONAL CODE	PDF 417, QRCode
	CHARACTER PER INCH		20.0 cpi / 15.0 cpi
INTERFACE	STANDARD		RS-232, Bi-Directional Parallel
	DEALER OPTION		RS-485; USB; 10/100 Base T Ethernet I/F
DATA BUFFER			4KB or 45 Bytes
PRINTER SPEED			7.9"/ Sec (200mm) Graphics and Text
			3.9"/ Sec in 2 Colour Print Mode
PAPER	DIMENSIONS (MM)	ROLL PAPER	79.5 ± 0.5 (W) x Diameter 83.0
	THICKNESS (MM)		0.06 to 0.07
POWER			24 VDC ± 7%
POWER CONSUMPTION			Approx. 1.8 A (Mean)
D.K.D. FUNCTION			2 Drivers
RELIABILITY	MTBF		360,000 Hours
	MCBF		52,000,000 Lines
	AUTO CUTTER		1.5 Million Cuts
DIMENSIONS (D X W X H)			195 x 145 x 148 mm
WEIGHT			Approx. 1.8 kg
CASE COLOUR			(ECW) Epson Cool White
			(EDG) Epson Dark Grey
POWER SUPPLY			PS-180
OPTION			Wall-Hanging Bracket WH-10
SAFETY STANDARDS			UL1950 / CSA / C22.2 No. 950





Epson is the registered trademark of SEIKO EPSON CORPORATION.

All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.



Tel: 0-2898-6470-1 Fax: 0-2898-6471 www.abt.co.th Dealer's Stamp