

# Zebra® GT800™ Desktop Printer



SEE MORE. DO MORE.



## Compact design with affordability, versatility and ease of use

Providing great performance and reliability at a competitive price, the GT800 direct-thermal/thermal-transfer desktop printer offers a wide range of advanced features to meet a variety of low-to-medium volume printing applications.

The GT800 printer supports both 74-metre and 300-metre ribbon capacities and, because its intelligent design means that no additional settings are required for supporting different roll lengths, it is easy for users to select the appropriate length for the task in hand.

Larger ribbon capacity (requiring less frequent replacement) and its simplicity of use combine with reliability and compact design to make this printer an ideal choice for commercial environments with moderate printing requirements.

With a full feature set and competitive pricing, the GT800 desktop printer provides an affordable route to Zebra quality.

## Intuitive and durable design

The intuitive design of the GT800 printer combines with a choice of three connectivity interfaces and optional 10/100 Ethernet, co-resident EPL2™ and ZPL II® programming languages, Unicode™ and optional ZBI 2.0™ to ensure that integration is quick and efficient.

Print speeds of up to 127mm per second, a powerful processor and memory allocation make label processing and throughput fast and easy whilst ongoing management of the product and operator intervention are kept to a minimum with status reporting, odometer control and increased ribbon capacity.

A durable, compact design supporting a range of media with widths of up to 114mm, the GT800 printer is an excellent choice for customers looking to migrate easily or upgrade from a competitor's thermal-transfer desktop printer.

## Ideal for these applications:

- **Healthcare**
  - Document archiving
  - Specimen labelling
  - Sterile services labelling
  - Thermal transfer patient identification
- **Manufacturing**
  - Agency labels
  - Product labelling
- **Retail**
  - Outdoor product labelling
  - Retail pharmacy labelling and safety labels
  - Speciality printing
- **Security**
  - Asset marking
  - Evidence tracking
- **Supply chain**
  - Product and shipping labels for outdoor use

# SPECIFICATIONS AT A GLANCE\*

## ZEBRA GT800 DESKTOP PRINTER

<b>Printer name</b> <ul style="list-style-type: none"> <li>GT800</li> </ul>	<b>Ribbon characteristics</b>	<b>Firmware</b>
<b>Standard features</b> <ul style="list-style-type: none"> <li>300- or 74-metre ribbon handling</li> <li>32-bit RISC processor</li> <li>Co-resident EPL2 and ZPL II programming languages</li> <li>Triple connectivity: serial, USB and parallel</li> <li>Print methods: thermal-transfer and direct-thermal modes; printing of barcodes, text and graphics</li> <li>OpenACCESS™ for easy media and ribbon loading</li> <li>Microsoft® Windows® drivers</li> <li>Odometer</li> <li>Unicode™</li> <li>ENERGY STAR®-compliant</li> <li>Intelligent clutch – no switching or additional setup required</li> <li>No secondary cores on genuine Zebra ribbon</li> </ul>	<b>Outside diameter</b> <ul style="list-style-type: none"> <li>66mm/2.6" (300m roll); 34mm/1.34" (74m roll)</li> </ul> <b>Standard length</b> <ul style="list-style-type: none"> <li>300m (984'); 74m (242')</li> </ul> <b>Ratio</b> <ul style="list-style-type: none"> <li>1:4 (one 300m roll of ribbon per four rolls of media)</li> <li>1:1 (one 74m roll of ribbon per roll of media)</li> </ul> <b>Width</b> <ul style="list-style-type: none"> <li>33.8mm/1.33" to 110mm/4.3"</li> </ul> <b>Core internal diameter</b> <ul style="list-style-type: none"> <li>300m ribbon: 25.4mm/1.00"</li> <li>74m ribbon: 12.7mm/0.5"</li> </ul>	<ul style="list-style-type: none"> <li>ZPL II: Zebra Programming Language provides sophisticated label formatting and printer control and is compatible with tabletop and mobile Zebra printers</li> <li>EPL2: Eltron Programming Language with Line Mode simplifies label formatting and enables format compatibility with legacy applications</li> <li>ZBI 2.0: a powerful programming language that lets printers run standalone applications, connect to peripherals and much more</li> <li>XML-enabled printing</li> </ul> <b>Networking/Connectivity</b> <ul style="list-style-type: none"> <li>Ethernet: internal 10/100 offered in combination with USB and serial interface (replaces parallel port)</li> </ul>
<b>Printer specifications</b>	<b>Operating characteristics</b>	<b>Fonts/Graphics/Symbologies</b>
<b>Resolution</b> <ul style="list-style-type: none"> <li>203dpi/8 dots per mm</li> </ul>	<b>Environment</b> <ul style="list-style-type: none"> <li>Operating temp.: 5°C/40°F to 41°C/105°F</li> <li>Storage temp.: -40°C/-40°F to 60°C/140°F</li> <li>Operating humidity: 10% to 90% non-condensing R.H.</li> <li>Storage humidity: 5% to 95% non-condensing R.H.</li> </ul>	<ul style="list-style-type: none"> <li>Unicode-compliant for multi-language applications</li> <li>16 resident expandable ZPL fonts</li> <li>One resident scalable ZPL font</li> <li>Five resident expandable EPL2 fonts</li> <li>Supports user-defined fonts and graphics, including custom logos</li> </ul>
<b>Media characteristics</b>	<b>Agency approvals</b>	<b>Barcode symbologies</b>
<b>Memory</b> <p>Standard: 8MB flash, 8MB SDRAM</p>	<b>Physical characteristics</b> <ul style="list-style-type: none"> <li>Width: 197mm/7.75"</li> <li>Height: 184mm/7.25"</li> <li>Depth: 273mm/10.75"</li> <li>Weight: 5kg/10.98lb</li> </ul>	<ul style="list-style-type: none"> <li>Barcode ratios: 2:1 (non-rotated) and 3:1 linear barcodes: Codabar, Code 11 (ZPL), Code 39, Code 93, Code 128, EAN-8, EAN-13, EAN-14 (ZPL), German Post Code (EPL), GS1 DataBar (formerly RSS), Industrial 2-of-5 (ZPL), Interleaved 2-of-5, ISBT-128 (ZPL), Japanese Postnet (EPL), Logmars (ZPL), MSI, Plessey, Postnet, Standard 2-of-5 (ZPL), UCC/EAN-128 (EPL), UPC-A, UPC and EAN 2 or 5 digit extensions (ZPL), UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E</li> <li>Two-dimensional barcodes: Aztec Code, Codablock (ZPL), Code 49 (ZPL), Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code</li> <li>For EPL and ZPL except where noted</li> </ul>
<b>Media sensors</b> <ul style="list-style-type: none"> <li>Fixed reflective and transmissive sensors</li> </ul>	<b>ZebraLink™ Solutions</b>	<b>Communication and interface capabilities</b>
<b>Print width</b> <ul style="list-style-type: none"> <li>104mm/4.09"</li> </ul>	<b>Software</b> <ul style="list-style-type: none"> <li>ZebraDesigner™ Pro: an intuitive, easy-to-use software program for creating complex label designs (option)</li> <li>ZebraDesigner: offers basic features for simple label design</li> <li>ZebraNet™ Bridge Enterprise: centrally manage Zebra printers from a single PC screen anywhere on your global network (unlicensed product free, licensed product option)</li> <li>ZebraNet Utilities v7.0: provides enhanced printing, conversion and administration capabilities; message management; and more</li> <li>ZebraDesigner Driver: the most powerful driver available from Zebra</li> <li>Web View: connect and control Zebra barcode printers via the printer's Web interface using a common Web browser and ZPL™</li> <li>Alert: printers equipped with ZebraNet print servers will notify you via any email-enabled wired or wireless device to minimise downtime</li> <li>POS driver</li> </ul>	<ul style="list-style-type: none"> <li>Centronics® parallel (36-pin) connector ports</li> <li>Auto-sensing RS-232 serial interface</li> <li>ZebraNet 10/100 Print Server (optional)</li> </ul>
<b>Print length</b> <ul style="list-style-type: none"> <li>991mm/39"</li> </ul>		<b>Options and accessories</b>
<b>Print speed</b> <ul style="list-style-type: none"> <li>203dpi: 127mm/5" per second</li> </ul>		<ul style="list-style-type: none"> <li>Dispenser – label peel and present with label-present sensor</li> <li>ZebraNet 10/100 Print Server – internal and external Ethernet options for network communication and printing</li> <li>KDU and KDU Plus™ – keyboard display units for standalone printing applications</li> </ul>
<b>Media thickness</b> <ul style="list-style-type: none"> <li>0.08mm/0.003" to 0.19mm/0.007"</li> </ul>		<b>Electrical specifications</b>
<b>Media types</b> <ul style="list-style-type: none"> <li>Roll-fed or fan-fold</li> <li>Label stock (die-cut or continuous, direct-thermal or thermal-transfer)</li> <li>Tag stock (die-cut or continuous, direct-thermal or thermal-transfer)</li> </ul>		<ul style="list-style-type: none"> <li>Auto-ranging external power supply with C5-type connector</li> <li>Output: 20VDC, 2.5A</li> <li>Input: 100–240VAC, 50–60Hz</li> </ul>



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด  
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.  
19/298 หมู่ 10 ถนนพระรามที่ 2 บางมด จอมทอง กรุงเทพฯ 10150  
19/298 Moo 10 Rama 2 Rd., Bangmod, Jomthong, Bangkok, 10150

Tel : 0-2898-6470-1  
Fax: 0-2898-6471  
www.abt.co.th

\*Specifications subject to change without notice.

©2013 ZIH Corp. EPL2, KDU Plus, OpenACCESS, ZebraDesigner, ZebraLink, ZebraNet, ZBI 2.0, ZPL and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Unicode is a trademark of Unicode, Inc. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ENERGY STAR is a registered trademark of the Environmental Protection Agency. Centronics is a registered trademark of Centronics Data Computer Corporation. All other trademarks are the property of their respective owners.