

Kowa

IR

Model : KW-274s IR



Features

- 1/3" Sony CCD sensor, 450 TV Lines
- Lens 3.6mm / Chip set Sony 3142+633
- Built-in 36 PCS Taiwan Tyntek IR LED
- Effective range up to 20M
- Weatherproofing criterion IP 66

Model	KW-274s IR
Image Device	1/3" SONY CCD
Picture Elements	PAL512(H) x 582(V) ; NTSC: 510(H) x 492(V)
Resolution	450 TVL
Min. Illumination	0.2 Lux / F2.0 (Day), 0 Lux (IR on)
S/N Ratio	More than 48dB
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000
Flickerless Mode	On/Off (NTSC:1/100, PAL:1/120)
Gamma	0.45
Lens Furnished	Board Lens 3.6mm / F2.0 (option:4/ 6/ 8/12/16mm)
White Balance	Auto
Sync. System	Internal
Video Output	1 Vp-p / 75 Ohms
Infrared Luminary	36 pieces IR-LED
Wavelength	850nm
Illumination Distance	20 M
Power Supply	DC12V±10%
Power Consumption	IR On:280mA max., IR Off:70mA max.
Operating Temp.	- 10°C ~ 50°C