



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.
106 ซ.พระรามที่2 ซอย42 ถ.พระราม2 แขวงบางมด เขตจอมทอง กรุงเทพฯ 10150
106 Soi Rama II 42, Rama II Rd., Bangmod Jomthong Bangkok 10150

Tel : 0-2898-6470-1
Fax: 0-2898-6471
www.abt.co.th

iNNEKT
Innovative Technology



MODEL		SPECIFICATIONS
Special function	P2P function	Using Device ID and password to login www.vssweb.net , realize remote monitoring, playback and control like IE Web No need any network, IP setting, easy for end user to use
System	Operation System	Embedded LINUX
	Pentaplex function	Live monitoring, recording, playback, backup & remote access
	Control Mode	Front panel, USB mouse, IR remote control, Network
Video	IP Camera Input	4ch.(64Mbps)
	Decoding Capability	4ch.D1@30fps 4ch.720P@30fps 2ch.1080P@30fps
	Support Protocol	ONVIF
	Standard	PAL (625line, 50f/s) NTSC (525line, 60f/s)
	Output	1 CVBS, BNC (1.0Vp-p,75 ohms)
		1 HDMI, 1.3a,support 1920×1080 Resolution 1 VGA,1920×1080,1280×1024,1024×768
Audio	Output	1 BNC (2.0Vp-p,300 ohms)
	Two-way Talk	1ch. standalone
Display	Frame	1-30fps
	Tour Display	Support
	Working Status Display	LCD,blue backlight(working temperature,recording status,error code
	Privacy Masking	Four zones for privacy masking for each channel
Recording	Video Compression	MPEG-4/H.264(High Profile@Level4.2)
	Audio Compression	G.711A
	Image Encoding	Adjustable encoding quality, variable code stream/fixed code stream
	Dual Stream	Support
	Recording Mode	Manual, scheduled, motion detection, stop
	Time bar	Support
Video Detection&Alarm	Trigger Events	Recording, PTZ, Tour,Email
	Motion Detection	396 (22×18) detection zone, variable sensitivity levels
	Capture	JPEG capture
	Alarm Input	4ch.
	Alarm Output	1ch.NO,NC
Playback&Backup	Max Playback	1/2/4 ch.
	Backup Mode	USB,HDD,Network Backup
Network	Ethernet	1 RJ-45 port (10M/100M)
	Network protocol	TCP/IP, UDP, HTTP, RTP/RTSP
	Network Functions	DHCP, PPPOE, DDNS,SMTP,SNTP,FTP,UPnP,P2P,3G
	Remote Operation	Monitoring,PTZ control,playback,system setting,file download,log
	Smart Phone	iPhone,iPad,Android
Hard Disk	Hard Disk	2 SATA ports,each SATA supports 4TB
	HDD Management	Hard disk hibernation technology, HDD faulty alarm&raid
Auxiliary Interface	USB Interface	2 USB 2.0 ports
	RS485	Standard 485, half duplex,PTZ control
POE Function	POE function	4 ch.
		IEEE 802.3af
		RJ45 10M/100M
Environment	Power Supply	DC12V/3.3A DC48V/1A(POE)
	Power Consumption	5W (without HDD&POE)
	Working Environment	-10℃ ~ +55℃ / 10% ~ 90%RH
	Dimension(W*D*H)	1U, 360x260x48 (mm)
	Weight	2Kg (without HDD)
	Installation	Desk type