

TSC

The Smarter Choice.

CELEBRATING 20 YEARS



TTP-244M PRO SERIES – Industrial Thermal Transfer Bar Code Printer THE LOW-COST LEADER IN ITS CLASS!



KEY FEATURES

- 4 MB Flash and 8 MB SDRAM
- Up to 102 mm (4") per second print speed
- Label gap sensor, black mark sensor & ribbon end sensor
- Wide selection of options, including the stand-alone keyboard display units, rotary cutter, peel-off kit, Bluetooth module, external 802.11 b/g/n wireless module and LCD control panel

APPLICATIONS

- Transportation
- Distribution
- Healthcare
- Manufacturing
- Business/Office



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.
106 ซ.พระรามที่2 ซอย42 ก.พระราม2 แขวงบางมด เขตจอมทอง กรุงเทพฯ 10150
106 Soi Rama II 42, Rama II Rd., Bangmod Jomthong Bangkok 10150

TEL: 02-898-6470-1

FAX: 02-898-6471

WWW:ABT-THAI.COM

TTP-244M PRO SERIES – Industrial Thermal Transfer Bar Code Printer

PRINTER MODEL	TTP-244M Pro	TTP-244ME Pro	TTP-342M Pro	TTP-342ME Pro
Resolution	8 dots/mm (203 DPI)		12 dots/mm (300 DPI)	
Printing method	Thermal transfer & Direct thermal			
Max. print speed	102 mm (4")/second		51 mm (2")/second	
Max. print width	104 mm (4.09")			
Max. print length	2,286 mm (90")		1,016 mm (40")	
Enclosure	Metal construction with view window			
Physical dimension	295 mm (W) x 220 mm (H) x 360 mm (D) 11.61" (W) x 8.66" (H) x 14.17" (D)			
Weight	8.7 kg (19.18 lbs)			
Label roll capacity	178 mm (7") OD			
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside)			
Ribbon width	25.4 mm ~ 110 mm (1" ~ 4.33")			
Processor	32-bit RISC CPU			
Memory	<ul style="list-style-type: none"> • 4 MB Flash • 8 MB SDRAM • SD card reader for Flash memory expansion, up to 4 GB 			
Interface	<ul style="list-style-type: none"> • RS-232 • Centronics • USB 2.0 	<ul style="list-style-type: none"> • RS-232 • USB 2.0 	<ul style="list-style-type: none"> • RS-232 • Centronics • USB 2.0 	<ul style="list-style-type: none"> • RS-232 • USB 2.0
Power	Internal universal switching power supply <ul style="list-style-type: none"> • Input: AC 100-240V, 1.8A, 50-60Hz • Output: DC 24V, 2.5A, 60W 			
LCD	<ul style="list-style-type: none"> • Graphic type, 122 x 32 pixel, with back light 	N/A	<ul style="list-style-type: none"> • Graphic type, 122 x 32 pixel, with back light 	N/A
Operation switch, button	1 power switch, 3 buttons (Menu, Pause/Select, Feed/Set)			
Sensors	<ul style="list-style-type: none"> • Gap transmissive sensor (position selectable) • Black mark reflective sensor • Ribbon end sensor • Head open sensor 			
Real time clock	Standard			
Internal font	<ul style="list-style-type: none"> • 8 alpha-numeric fonts 			
Bar code	<ul style="list-style-type: none"> • 1D barcode Code39, Code39C, Code93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2-digit, 5-digit add-on, MSI, PLESSEY, POSTNET, ITF14, code 11, China Posst, GS1 DataBar • 2D barcode PDF-417, Maxicode, Datamatrix, QR code, Aztec 			
Font & barcode rotation	0, 90, 180, 270 degrees			
Command set	TSPL, TPLE			
Media type	Roll-fed, fan-fold, continuous, die-cut, black mark, ticket, tag, textile (outside wound)			
Media width	25.4 mm ~ 114 mm (1.0" ~ 4.49")			
Media thickness	0.06 mm ~ 0.25 mm (2.36 ~ 9.84 mil)			
Media core diameter	25.4 mm ~ 76.2 mm (1" ~ 3")			
Label length	6 ~ 2,286 mm (0.2" ~ 90")		6 ~ 1,016 mm (0.2" ~ 40")	
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing			
Safety regulation	CCC, CE Class A			
Environmental concern	Comply with RoHS, WEEE			
Accessories	<ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • USB cable • Power cord • Ribbon spindle x 2 • Ribbon paper core 			
Limited warranty	<ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first 			
Factory options	N/A	<ul style="list-style-type: none"> • 122 x 32 pixels graphic type LCD display with back light • Centronics parallel interface 	N/A	<ul style="list-style-type: none"> • 122 x 32 pixels graphic type LCD display with back light • Centronics parallel interface
Dealer options	<ul style="list-style-type: none"> • Rotary cutter (full cut) • Peel-off module 			



CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: printer_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: printer_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc. Corporate Office
Tel: +1 909 525 9779
E-mail: sales@tscprinters.com

Orlando Office

Tel: +1 407 704 8918
E-mail: sales@tscprinters.com

CANADA

TSC Auto ID Technology America Inc.
Tel: +1 909 525 9779
E-mail: sales@tscprinters.com

MEXICO

TSC Mexico Representative Office
Tel: +52 (33) 3836 6682
E-mail: sales@idc-componentes.com

BRAZIL

TSC Brazil Representative Office
Tel: +55 (11) 9597 8098
E-mail: sales@tscprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 00
E-mail: info@tsceu.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
Tel: +7 915 422 8889
E-mail: info@tsceu.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: info@tscmea.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: printer_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: sale@tscprinters.com.cn



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.

106 ซ.พระรามที่ 2 ซอย 42 น.พ.ระมาน 2 แขวงบางมด เขตจอมทอง กรุงเทพฯ 10150
106 Soi Rama II 42, Rama II Rd., Bangmod Jomthong Bangkok 10150

TEL: 02-898-6470-1

FAX: 02-898-6471

WWW:ABT-THAI.COM

TSC is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2013 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.