

# TSC

The Smarter Choice.



## TTP-245C SERIES – Desktop Thermal Transfer Bar Code Printer THE PERFECT FIT!



### KEY FEATURES

- Perfect size – space saving design
- Fast Processor 200 MHz
- Standard memory of 4 MB Flash, 8 MB SDRAM and SD card reader for memory expansion up to 4 GB
- High quality double-walled clamshell design
- Easy ribbon loading
- Easy media loading
- Durability and reliability
- USB 2.0, serial, parallel and Ethernet interfaces are standard
- Powerful firmware: TSPL-EZ™, file manager, BASIC programming, stand-alone programming
- 2-year limited warranty
- ENERGY STAR® qualified

### APPLICATIONS

- Point-Of-Sale
- Product Marking
- Receipt / Coupon Printing
- Compliance Labeling
- Asset Tracking
- Document Management
- Shipping / Receiving
- Specimen Labeling
- Inventory Control
- Patient Tracking



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด  
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.  
106 ซ.พระรามที่2 ซอย42 ก.พระราม2 แขวงบางมด เขตจอมทอง กรุงเทพฯ 10150  
106 Soi Rama II 42, Rama II Rd., Bangmod Jomthong Bangkok 10150

TEL: 02-898-6470-1

FAX: 02-898-6471

WWW: ABT-THAI.COM

/// [www.tscprinters.com](http://www.tscprinters.com)

# TTP-245C SERIES – Desktop Thermal Transfer Bar Code Printer

PRINTER MODEL	TTP-245C	TTP-343C	TTP-244CE (BASIC)	TTP-244CE (ADVANCED)
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)	8 dots/mm (203 DPI)	
Printing method	Thermal Transfer & Direct Thermal			
Max. print speed	152 mm (6")/second	102 mm (4")/second	102 mm (4")/second	
Max. print width	108 mm (4.25")	106 mm (4.17")	108 mm (4.25")	
Max. print length	2,286 mm (90")	1,016 mm (40")	2,286 mm (90")	
Enclosure	Double-walled plastic			
Physical dimension	202mm (W) x 173 mm (H) x 258 mm (D) 7.95" (W) x 6.81" (H) x 10.16" (D)			
Weight	2.3 kg (5.07 lbs)			
Label roll capacity	127 mm (5" ) OD			
Ribbon	110 m long, max. OD 40 mm, 0.5" core (ink coated outside)			
Ribbon width	40 mm ~ 110 mm (1.57" ~ 4.33")			
Processor	32-bit RISC CPU			
Memory	<ul style="list-style-type: none"> <li>4 MB Flash memory</li> <li>8 MB SDRAM</li> <li>SD Flash memory card reader for Flash memory expansion, up to 4 GB</li> </ul>		<ul style="list-style-type: none"> <li>4 MB Flash memory</li> <li>8 MB SDRAM</li> </ul>	<ul style="list-style-type: none"> <li>4 MB Flash memory</li> <li>8 MB SDRAM</li> <li>SD Flash memory card reader for Flash memory expansion, up to 4 GB</li> </ul>
Interface	<ul style="list-style-type: none"> <li>RS-232</li> <li>Centronics</li> <li>USB 2.0</li> <li>Internal Ethernet, 10/100 Mbps</li> <li>Bluetooth (user option)</li> <li>External 802.11 b/g/n wireless (user option)</li> </ul>		<ul style="list-style-type: none"> <li>USB 2.0</li> </ul>	<ul style="list-style-type: none"> <li>USB 2.0</li> <li>RS-232</li> <li>Centronics</li> <li>Internal Ethernet, 10/100 Mbps</li> <li>Bluetooth (user option)</li> <li>External 802.11 b/g/n wireless (user option)</li> </ul>
Power	External universal switching power supply <ul style="list-style-type: none"> <li>Input: AC 100-240V, 2.5A, 50-60 Hz</li> <li>Output: DC 24V 3.75A, 90W</li> </ul>		External universal switching power supply <ul style="list-style-type: none"> <li>Input: AC 100-240V, 2.5A, 50-60 Hz</li> <li>Output: DC 24V, 2.5A, 60W</li> </ul>	
Operation switch, button LED	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)			
Sensors	<ul style="list-style-type: none"> <li>Gap transmissive sensor</li> <li>Black mark reflective sensor (position adjustable)</li> <li>Head open sensor</li> <li>Ribbon end sensor</li> </ul>			
Internal fonts	<ul style="list-style-type: none"> <li>8 alpha-numeric bitmap fonts</li> <li>Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> </ul>			
Bar code	<ul style="list-style-type: none"> <li>1D bar code Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, GS1 DataBar, Logmars, Code 11</li> <li>2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec</li> </ul>			
Font and barcode rotation	0, 90, 180, 270 degree			
Printer language	TSPL-EZ™			
Media type	Continuous, die-cut, tag & fan-fold (outside wound)			
Media width	20 ~ 112 mm (0.79" ~ 4.4")			
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)			
Media core diameter	25.4 ~ 38.1mm (1" ~ 1.5")			
Label length	10 ~ 2,286 mm (0.39" ~ 90")	10 ~ 1,016 mm (0.39" ~ 40")	10 ~ 2,286 mm (0.39" ~ 90")	
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing			
Safety regulation	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC, ENERGY STAR®			
Environmental concern	Comply with RoHS, WEEE			
Accessories	<ul style="list-style-type: none"> <li>Windows labeling software CD disk</li> <li>Quick start guide</li> <li>External universal switching power supply</li> <li>USB cable</li> <li>Power cord</li> </ul>			
Limited warranty	<ul style="list-style-type: none"> <li>Printer: 2 years</li> <li>Print head: 25 km (1 million inches) or 12 months which comes first</li> <li>Platen: 50 km (2 million inches) or 12 months which comes first</li> </ul>			
Factory options	<ul style="list-style-type: none"> <li>Real time clock (standard in EMEA)</li> </ul>		<ul style="list-style-type: none"> <li>N/A</li> </ul>	
Dealer options	<ul style="list-style-type: none"> <li>Guillotine cutter (full cut or partial cut)</li> <li>Peel-off module</li> </ul>		<ul style="list-style-type: none"> <li>N/A</li> </ul>	
User options	<ul style="list-style-type: none"> <li>Bluetooth module (serial interface)</li> <li>802.11 b/g/n wireless module (serial interface)</li> <li>External media hanger with 3" OD label spindle</li> <li>KP-200 Plus series keyboard</li> <li>KU-007 Plus programmable smart keyboard</li> </ul>		<ul style="list-style-type: none"> <li>External media hanger with 3" OD label spindle</li> </ul>	<ul style="list-style-type: none"> <li>Guillotine cutter (full cut or partial cut)</li> <li>Peel-off module</li> <li>External media hanger with 3" OD label spindle</li> <li>Bluetooth module (serial interface)</li> <li>802.11 b/g/n wireless module (serial interface)</li> </ul>



## CORPORATE HEADQUARTERS

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 2 2218 6789  
E-mail: apac\_sales@tscprinters.com

## LI ZE PLANT

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 3 990 6677  
E-mail: apac\_sales@tscprinters.com

## AMERICAS

**TSC Auto ID Technology America Inc. Corporate Office**  
Tel: +1 909 612 9606  
E-mail: americas\_sales@tscprinters.com

## Orlando Office

Tel: +1 407 704 8918  
E-mail: americas\_sales@tscprinters.com

## CANADA

**TSC Auto ID Technology America Inc.**  
Tel: +1 909 612 9606  
E-mail: americas\_sales@tscprinters.com

## MEXICO

**TSC Mexico Representative Office**  
Tel: +52 (33) 3836 6682  
E-mail: americas\_sales@tscprinters.com

## BRAZIL

**TSC Brazil Representative Office**  
Tel: +55 (11) 9597 8098  
E-mail: americas\_sales@tscprinters.com

## EMEA

**TSC Auto ID Technology EMEA GmbH**  
Tel: +49 (0) 8106 37979 00  
E-mail: emea\_sales@tscprinters.com

## RUSSIA

**TSC Auto ID Technology EMEA GmbH**  
Tel: +7 915 422 8889  
E-mail: emea\_sales@tscprinters.com

## MIDDLE EAST

**TSC Auto ID Technology ME Ltd, FZE**  
Tel: +971 4 2533 069  
E-mail: emea\_sales@tscprinters.com

## ASIA PACIFIC

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 2 2218 6789  
E-mail: apac\_sales@tscprinters.com

## CHINA

**Tianjin TSC Auto ID Technology Co., Ltd.**  
Tel: +86 22 5981 6661  
E-mail: apac\_sales@tscprinters.com



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด  
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.  
106 ซ.พระรามที่ 2 ซอย 42 ต.พระราม 2 แขวงบางมด เขตจอมทอง กรุงเทพฯ 10150  
106 Soi Rama II 42, Rama II Rd., Bangmod Jomthong Bangkok 10150

TEL: 02-898-6470-1  
FAX: 02-898-6471  
WWW.ABT-THAI.COM

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.  
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.  
© 2015 TSC Auto ID Technology Co., Ltd.  
Product models and Specifications are subject to change without notice.  
Contact your TSC sales representative for specific information.