

CCTV Competitive Hybrid Network DVR

TVI 5MP+AHD 1080p+CVI 1080p+960H/D1+IP Camera



RMH-0828EU-101C

- Up to 5MP (2592 x 1920) TVI camera supported
- Support TVI, AHD, CVI analog camera and IP Camera
- Support OSD setting over coaxial (UTC)
- Support IP camera with Onvif Profile protocol (V2.4)
- Cross device function for redundant recording
- Ideal for project bid, public place like airport, bank, and administration
- Excellent picture quality



MADE IN TAIWAN

CEFC RoHS

RMH Competitive

RMH-0828EU-101C

Front Panel : 1



Rear Panel : E-1



Dimension (mm) : 250(w)x215(d)x45(h)

Model		RMH-0828EU-101C
Camera Input		8CH AHD ,TVI ,CVI, IPC Hybrid
Housing		1
Video	Input	TVI:5MP@12/10 fps, 4MP@15/12 fps, 3MP@18/15 fps, 1080p@30/25 fps, 720p@60/50 fps, 720p@30/25 fps AHD:1080p@30/25 fps, 720p@60/50 fps, 720p@30/25 fps CVI:1080p@30/25 fps, 720p@60/50 fps, 720p@30/25 fps 960H/D1
	Output	1 HDMI with Audio and 1 VGA (Max. 1920 x 1080)
Audio	Input	4 RCA
	Output	1 RCA
System	Operating System	Embedded Linux OS
	SATA Devices	Max. 2 x SATA Device (HDD x 1)
	External HDD	N/A
	Alarm In /Relay Out	N/A
	Serial Interface	RS-485
	USB 2.0 Ports	USB2.0 X2
	Dimension (mm)	250mm(W)X215mm(D) X45mm(H)
	Power Rating	12V 2A, 24W
Display	Split Screen	1,4, SEQ.
	Auto Channel Switching	Switching time : 1 ~ 99 sec
	Mode	Zoom, Auto SEQ.
Recording	Compression	H.264 High Profile
	Main (Recording) Resolution	2590 x 1920, 2590 x 1520, 2048 x 1520, 1920 x 1080, 1280 x 720; 944 x 480 .704 x 480, 352 x 240 (NTSC) / 944 x 576 ,704 x 576, 352 x 288 (PAL)
	Sub (Network) Resolution	640 x 360 / 352 x 240, 176 x 120 (NTSC) / 352 x 288, 176 x 144 (PAL)
	Picture Quality	10~100 levels for adjustment
	Mode	Continuous, Event, Schedule
	Record Rate	NTSC 5MP 48fps ; 4MP 60fps ; 3MP 80fps ; 1080p 120fps ; 720p 240fps NTSC 5MP 40fps ; 4MP 50fps ; 3MP 66fps ; 1080p 100fps ; 720p 200fps
	Pre-Alarm	1 ~ 5 SEC
	Post-Alarm	1 ~ 100 SEC
Playback	Search Mode	Date/time, Event
	Zoom	*Digital (x2 ~ x5)
Network	Network Interface	10/100 Ethernet
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS
	Application	Windows 7 & 8, Mac OS X
	Remote Software	SoCatch, IE Browser, iCMS Pro
	Account	1 Admin + 10 Users
Backup	Mobile Device	Windows Phone 7.8, iPhone, iPad, Android
	Interface	USB or SATA
	AudioBackup	YES
Alarm	Backup Type	Network, ext. USB flash device , SATA optical DVD..etc.
	Motion Detection	Sensitivity: 100 levels for each channel Area: Programmable individually
OSD&DVR Control	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)
	Multi-Language	Supported
	Camera Title	Multi-Language
	USB Mouse	YES
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)
	Remote Controller	IR Remote Control
	System Upgrade	USB Flash Drive, iWatch DVR
General	Pan/Tilt/Zoom Control	Control From RS485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)
	Operating Temperature	-10°C ~ +55°C (14°F ~ 131°F)
	Operating Humidity	10%~80%

All specifications are subject to change without notice.



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.
106 ซ.พระรามที่ 2 ซอย 42 น.พระราม 2 แขวงบางมด เขตจอมทอง กรุงเทพฯ 10150
106 Soi Rama II 42, Rama II Rd., Bangmod Jomthong Bangkok 10150

TEL: 02-898-6470-1
FAX: 02-898-6470#13
WWW.ABT-THAI.COM