

SNBC

Extraordinary
Value!

BTP-M280A

Impact Receipt Printer



Preferred for POS, Bar & Kitchen Printer Applications

The BTP-M280A produces either receipts or kitchen orders faster than other popular impact printers. Featuring trouble-free drop-and-print paper loading, it is adjustable to accommodate 76, 70, or 58mm paper rolls. Print is clear and precise, allowing you to print long-lasting receipts with coupons, rebates and specials. User defined graphic logos are easily downloaded with SNBC's free utility software.

- Auto-Cutter and Paper Take-Up
- Serial, Parallel, Ethernet and Wireless WiFi Interface Options
- Two Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Stores and Prints Logo Images
- Extraordinary Reliability
- Contains Everything Necessary in the Carton – Including Communications Cables



BTP-M280A Impact Receipt Printer



Drop and Print Paper Loading with Built-In Paper Width Selector



Built-In Wall Mount Capability and Optional Audio/Visual Print Messenger



Conceal the Power Supply in the Optional Power Supply Cover



Includes Everything Necessary in the Carton Cover

Features

Proven impact printing technology preferred for POS kitchen printer applications.

- Everything You Need is in the Carton
- Serial, Parallel, Ethernet, USB and Wireless WiFi Interface Boards Available
- Uses the Same Interface Boards as Other SNBC Printers
- Auto-Cutter with Selectable Full or Partial Cut
- Two-Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Fast 4.7 Lines per Second Print Speed
- Drop and Print Paper Loading
- Built-In Wall Mount Capability
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches
- Includes Starter Paper Roll, Paper Width Selector, Appropriate Communications Cable, Power Adapter and Cord, Ribbon, CD-ROM with Drivers, Utilities and User's Manual

Optional Devices / Upgrades

Upgrade your printer with these easy-to-add options:

- Serial, Parallel, Ethernet and Wireless WiFi Interface Boards Are User Interchangeable
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed
- Power Supply Cover
- Powered USB Cable

Ports and Connectivity

A Choice of Serial (Shown), Parallel, USB, Ethernet or Wireless WiFi Interface Boards Available

B Cash Drawer

C DC 24V Power-In

Specifications

Max. Print Speed:	4.7 Lines per Second / 19.6mm per Second
Printing Method:	Impact
Characters Per Line – Font A:	33 / 35
Font B:	40 / 42
Characters Size – Font A:	9 x 9
Font B:	7 x 9
Paper Roll Type – Width:	76 / 69.5 / 57.5mm ± 0.5mm
Maximum Diameter:	83mm
Paper Thickness:	0.06mm ~ 0.085mm
Auto Paper Cutting Method:	Auto-Cutter with Selectable Full or Partial Cut
Inking Supply:	ERC-38 Ribbon Cartridge (Black/Red)
Reliability – MTBF:	180,000 Hours
MCBF:	18,000,000 Lines
Printhead Life:	150,000,000 Characters
Cutter Life:	1,500,000 Cuts
Character Set – Alphanumeric:	95
International:	13
Graphic:	128 x 8 Page
Interpreter:	ESC/POST™
Interface:	Serial / Parallel / Ethernet / USB / Wireless WiFi
Drivers – 32 bit:	POSReady 2009 / 2000 Server / 2000 Prof. / XP Home
32 and 64 bit:	Win 8 / Win 7 / Server 2008 / Server 2003 / XP Prof. / Vista
Drawer Port:	2 Port (+24VDC) with Drawer Compulsion
Data Buffer– Rec. Buffer RAM:	4 KB RAM
RAM Bitmap:	8 KB
Flash Bitmap:	128 KB
Power Supply:	AC 100 ~ 240 V, 50/60 Hz Adapter Included
Current/Power Usage:	1.5A / 36W
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)
Operating Humidity:	20% ~ 90% RH (Non-Condensing)
Dimensions:	6-5/16"W x 6-5/8"H x 11-3/4"D
Shipping Weight:	10.10 lbs.
Safety and EMI:	FCC / RoHS

