

TSC

The Smarter Choice.

CELEBRATING 20 YEARS



TTP-244 PRO – Desktop Thermal Transfer Bar Code Printer **AFFORDABLE PRICE, FAST PERFORMANCE, WON'T BREAK YOUR BAR CODE BUDGET**



KEY FEATURES

- 200 MHz 32-bit RISC processor with 8 MB SDRAM, 4 MB Flash memory
- Internally scalable true type fonts
- TSPL-EZ™ firmware emulates Eltron® and Zebra® languages out of the box
- Dual-motor gear driven design
- 300 meter (984') ribbon supply on a 25.4 mm (1") core (coated side out)
- 110 mm (4.3") OD internal media supply, optional external roll mount supports 214 mm (8.4") OD label rolls on 76.2 mm (3") core
- 5 inches per second print speed
- USB 2.0 & RS-232 interfaces standard
- Free bundled labeling software and Windows drivers
- Features an industry best 2 years limited warranty

APPLICATIONS

- Shipping & Receiving
- Compliance Labeling
- Asset Tracking
- Inventory Control
- Document Management
- Shelf Labeling & Product Marking
- Specimen Labeling & Patient Tracking

TTP-244 PRO – Desktop Thermal Transfer Bar Code Printer

| PRINTER MODEL | TTP-244 PRO |
|-------------------------------|---|
| Resolution | 8 dots/mm (203 DPI) |
| Printing method | Thermal Transfer & Direct Thermal |
| Max. print speed | 127 mm (5")/second |
| Max. print width | 108 mm (4.25") |
| Max. print length | 2,286 mm (90") |
| Enclosure | ABS plastic |
| Physical dimension | 232 mm (W) x 156 mm (H) x 288 mm (D) 9.13" (W) x 6.14" (H) x 11.34" (D) |
| Weight | 2.5 kg (5.51 lbs) |
| Label roll capacity | 110 mm (4.33") OD |
| Ribbon | 300 m long, max. OD 67 mm, 1" core (ink coated outside) |
| Ribbon width | 40 mm ~ 110 mm (1.6" ~ 4.3") |
| Processor | 32-bit RISC CPU |
| Memory | <ul style="list-style-type: none"> • 4 MB Flash memory • 8 MB SDRAM • SD card reader for Flash memory expansion, up to 4 GB (user option) |
| Interface | <ul style="list-style-type: none"> • USB 2.0 • RS-232 • Centronics (factory option) • Bluetooth (user option) • External 802.11 b/g/n wireless (user option) |
| Power | External universal switching power supply <ul style="list-style-type: none"> • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 2.5A, 60W |
| Operation switch, button, LED | 1 power switch, 1 feed button & 3 LED (Power, Error, On-line) |
| Sensors | <ul style="list-style-type: none"> • Gap transmissive sensor • Black mark reflective sensor • Ribbon end sensor |
| Internal fonts | <ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font |
| Bar code | <ul style="list-style-type: none"> • 1D bar code Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11 • 2D bar code PDF-417, Maxicode, DataMatrix, QR Code, Aztec |
| Font and barcode rotation | 0, 90, 180, 270 degree |
| Printer language | TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II) |
| Media type | Continuous, die-cut, black mark, fan-fold, notched (outside wound) |
| Media width | 25.4 ~ 112 mm (1.0" ~ 4.4") |
| Media thickness | 0.06 ~ 0.25 mm (2.36 ~ 9.84 mil) |
| Media core diameter | 25.4 ~ 76.2 mm (1" ~ 3") |
| Label length | 10 ~ 2,286 mm (0.39" ~ 90") |
| Environment condition | Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing |
| Safety regulation | FCC Class A, CE Class A, C-Tick Class A, TÜV/Safety, CCC |
| Environmental concern | Comply with RoHS, WEEE |
| Accessories | <ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • Power cord • External universal switching power supply • Label spindle, fixing tab x 2 • Ribbon spindle x 2 • Ribbon paper core |
| Limited warranty | <ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first |
| Factory options | • Centronics parallel & RS-232 serial interfaces |
| Dealer options | N/A |
| User options | <ul style="list-style-type: none"> • Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • External roll mount, media OD. 214 mm (8.4") on a 1" or 3" core • SD Flash memory card reader • 3" core label spindle • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard |



TSC
The Smarter Choice.
CELEBRATING 20 YEARS

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2014 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.



บริษัท แอดวานซ์ บิซิเนส เทคโนโลยี จำกัด
ADVANCE BUSINESS TECHNOLOGY CO.,LTD.

106 ซ.พระรามที่ 2 ซอย 42 ถ.พระราม 2 แขวงบางมด เขตจอมทอง กรุงเทพฯ 10150
106 Soi Rama II 42, Rama II Rd., Bangmod Jomthong Bangkok 10150

TEL: 02-898-6470-1

FAX: 02-898-6470#13

WWW.ABT-THAI.COM